

一次調壓閥

JRV-FF12/FF21P



Applicable Fluid: Air/Gas, Liquid

Working Pressure: Max 1.56MPa(16.0kgf/cm²)

Applicable Pressure: 0.04~1.17MPa
(0.5~12.0kgf/cm²)

Applicable Temperature: Max. 150°C

Size: 15A~150A

Connection: JIS 10K, 20K

Material: Cast Iron, Carbon Steel, Bronze, Stainless Steel

低溫安全閥和控制閥

JSV-PF11



Applicable Fluid: LNG/LPG

Applicable Pressure: 0.025~0.25MPa
(0.25~2.55kgf/cm²)

Applicable Temperature: -196~125°C

Size: 25A~250A

Connection: ASME Flange Type

Material: Stainless Steel

JSV-PF11



Applicable Fluid: LNG/LPG

Applicable Pressure: 0.1~0.3MPa
(1.0~3.05kgf/cm²)

Applicable Temperature: -196~125°C

Size: 25A~80A

Connection: ASME Flange Type

Material: Stainless Steel

JCV-CF11



Applicable Fluid: LNG/LPG

Applicable Pressure: 0.1~0.5MPa
(1.0~5.09kgf/cm²)

Applicable Temperature: -196~80°C

Size: 25A~200A

Connection: ASME Flange Type

Material: Stainless Steel

減壓閥

JRV-ST11



Applicable Fluid: Steam

Applicable Pressure Inlet: 0.98MPa(10.0kgf/cm²)
Outlet: 0.02 ~ 0.39MPa(0.2 ~ 4.0kgf/cm²)

Max.Reducing ratio 20:1

Applicable Temperature: Max. 184°C

Size: 15A ~ 40A

Connection: PT

Material: Cast Iron

JRV-ST17



Applicable Fluid: Air/Gas, Liquid

Applicable Pressure Inlet: 0.98MPa(10.0kgf/cm²)
Outlet: 0.03 ~ 0.39MPa(0.35 ~ 4.0kgf/cm²)

Max.Reducing ratio 10:1

Applicable Temperature: Max. 80°C

Size: 15A ~ 40A

Connection: PT

Material: Cast Iron

JRV-SF14/SF24D



Applicable Fluid: Air/Gas, Liquid

Applicable Pressure
Inlet: 1.96MPa(20.0kgf/cm²)
Outlet: 0.05 ~ 1.18MPa(0.5 ~ 12.0kgf/cm²)

Max.Reducing ratio 10:1

Applicable Temperature: Max. 80°C

Size: 15A ~ 150A

Connection: JIS 10K, 20K

Material: Cast Iron, Bronze, Cast Steel

JRV-SF12/SF24P



Applicable Fluid: Air/Gas, Liquid

Applicable Pressure
Inlet: 1.96MPa(20.0kgf/cm²)
Outlet: 0.05 ~ 1.18MPa(0.5 ~ 12.0kgf/cm²)

Max.Reducing ratio 10:1

Applicable Temperature: Max. 150°C

Size: 15A ~ 150A

Connection: JIS 10K, 20K

Material: Cast Iron, Bronze, Cast steel

減壓閥

JRV-SF16/SF21



Applicable Fluid: Steam

Applicable Pressure Inlet: 1.96MPa(20.0kgf/cm²)
Outlet: 0.03~1.56MPa(0.35~16.0kgf/cm²)

Max.Reducing ratio 20:1

Applicable Temperature: Max. 300°C

Size: 15A~200A

Connection: JIS 10K, 20K

Material: Cast Iron, Carbon Steel

JRV-SF31



Applicable Fluid: Air/Gas, Liquid

Applicable Pressure Inlet: 2.94MPa(30.0kgf/cm²)
Outlet: 0.05~1.47MPa(0.5~15.0kgf/cm²)

Max.Reducing ratio 10:1

Applicable Temperature: Max. 80°C

Size: 15A~40A

Connection: JIS 10K, 20K, 30K

Material: Carbon Steel