

温度控制閥

JTC-DF12



Type: Direct Acting

Applicable Fluid: Steam, Hot Water, Oil

Applicable Pressure:
0.05 ~ 0.98MPa(0.5 ~ 10.0khf/cm²)

Applicable Temperature: Max. 220°C

Adjustable Temperature: 40 ~ 110°C

Size: 15A ~ 40A

Connection: JIS 5K, 10K, 16K

Material: Cast Iron, Bronze, Carbon Steel

JTC-PF16



Type: Pilot Acting

Applicable Fluid: Steam, Hot Water, Oil

Applicable Pressure:
0.05 ~ 0.98MPa(0.5 ~ 10.0khf/cm²)

Applicable Temperature: Max. 220°C

Adjustable Temperature: 40 ~ 110°C

Size: 15A ~ 200A

Connection: JIS 10K, 16K

Material: Cast Iron, Bronze, Carbon Steel

JTC-DF13



Type: Bellows

Applicable Fluid: Steam, Hot Water, Oil

Applicable Pressure:
0.05 ~ 1.59MPa(0.5 ~ 16.0khf/cm²)

Applicable Temperature: Max. 220°C

Adjustable Temperature: 40 ~ 110°C

Size: 15A ~ 40A

Connection: JIS 5K, 10K, 16K

Material: Cast Iron, Bronze, Carbon Steel