

疏水閥

JTR-FT12/FF12



Type: Ball Float

Applicable Fluid: Steam

Applicable Pressure: 0.44, 0.98, 1.37MPa(4.5, 10.0, 14.0kgf/cm²)

Applicable Temperature: Max. 220°C

Size: 15A~50A

Connection: PT, JIS 10K, 16K

Material: Cast Iron, Carbon Steel

JTR-DT22/DF21



Type: Thermodynamic Disc

Applicable Fluid: Steam

Applicable Pressure: 0.03~1.56MPa(0.35~16.0kgf/cm²)

Applicable Temperature: Max. 220°C

Size: 15A~50A

Connection: PT, JIS 10K, 16K

Material: Cast Iron, Ductile Iron

JTR-DT31



Type: Thermodynamic Disc

Applicable Fluid: Steam

Applicable Pressure: 0.03~2.94MPa(0.35~30.0kgf/cm²)

Applicable Temperature: Max. 400°C

Size: 8A~10A

Connection: PT

Material: Stainless Steel

JTR-DT41/DF41



Type: Thermodynamic Disc

Applicable Fluid: Steam

Applicable Pressure: Max. 4.11MPa(42.0kgf/cm²)

Applicable Temperature: Max. 400°C

Size: 15A~50A

Connection: PT, JIS 10K, 16K, 20K

Material: Stainless Steel

疏水閥

JTR-DS70/DF70



Type: Thermodynamic Disc

Applicable Fluid: Steam

Applicable Pressure: Max. 6.37MPa(65.0kgf/cm²)

Applicable Temperature: Max. 525°C

Size: 15A~25A

Connection: SW, AMSE 600LB, 900LB

Material: Alloy Steel (A182-F22)

Air Vent

JAV-FF11



Type: Ball Float

Applicable Fluid: Water, Oil

Applicable Pressure: Max. 1.56MPa(16.0kgf/cm²)

Applicable Temperature: Max. 220°C

Size: 15A~25A

Connection: JIS 10K, 16K, 20K

Material: Carbon Steel